

D34 POWER PACK DESCRIPTION OPOWEKU334



The D34 is a diesel driven hydraulic power pack with two variable flow hydraulic circuits. Driven by a powerful 43hp / 36kW water-cooled diesel engine driving twin fixed displacement hydraulic pumps, mounted in painted steel frame. Fork lift pockets, central lift point, hydraulic oil and fuel tanks are all incorporated in this compact unit. Twin hydraulic flow controls, gauges and stainless steel hydraulic couplings. Spin on return filter, fluid level and temp gauges, tank top filler/strainer.

Specification

Drive:	43.7 hp / 32.6 kW Int. Tier 4 Stage IIIA (34.7 hp / 25.9 kW Net Continuous) (2800 rpm) water-cooled diesel engine with 12 volt electric start. (34.7hp continuous rating)
Max Hydraulic Output	
Circuit 1:	16 gpm / 60 litres er min @ 2700 psi / 186 bar
Circuit 2:	7 gpm / 23 litres per min @ 2500 psi / 172 bar
Hydraulic Tank:	40 gallons / 152 litres
Fuel Tank:	25 gallons / 94 litres
Hydraulic Quick Couplings:	Stainless Steel
Lifting:	Central Lift Point
Fabric Cover:	Included
Dimensions:	74 x 27 x 44 inch / 1.88 x 0.69 x 1.12 m
Weight:	1,080 lb (dry) 1,543 lb (wet) / 490 kg (dry) 700 kg (wet)