

1309 W. Main St. Carmi, IL 62821 Tel: +1 (618) 382 2525 Fax: +1 (618) 382 3610 E-mail: elastec@elastec.com Web Page: www.elastec.com

E25 ELECTRIC HYDRAULIC POWER UNIT



The E25 is a portable electric motor-driven hydraulic power unit for operating a range of equipment. Typically it is packaged with drum skimmers fitted with our ES400 recovered oil transfer pump.

The Elastec E25 Electric Hydraulic Power Pack features a quiet-running electric motor mounted in a steel cage frame fitted with controls. Four large anti-vibration feet are installed at the corners of the frame. The E25 has a laser-cut control panel with valves to control flow to the two hydraulic circuits (skimmer and pump). Twin hydraulic pressure gauges show the working pressures. The hydraulic tank is mounted above the hydraulic pump and is fitted with level / temperature gauge, filter and filler / strainer.

Specification:

Drive:	25 hp 220 v / 440 v 3 Phase 60 Hz Electric Motor available in TEFC or EXP
Max Hydraulic Output (tandem pump):	Skimmer 5 gpm / 19 lpm @ 2,500 psi / 172 bar ES400 Pump 11 gpm / 41 lpm @ 2,700 psi / 186 bar Variable speed controls
Frame:	Skid mount with lifting bracket
Hydraulic Tank:	25 gallons / 94 litres. Spin on return filter, fluid level and temp gauges, tank top filler/strainer.
Hydraulic Connections:	Stainless steel quick couplings
Lifting:	Central lift point
Dimension:	56.5 x 26 x 48.5 inch / 144 x 66 x 124 cm
Fabric Cover:	Included