

MINIVAC III (DIESEL)



The ELASTEC MiniVac III can generate high levels of air flow and vacuum due to the vane pump design, making it ideal for working in industrial locations. The vacuum can be applied to our optional Hopper system or alternative suitable vacuum vessels.

This vacuum system is good for cleaning liquids, wet solids, grit, sludge from tanks, sumps and pits.

Note: not for dust or hazardous applications

Specification

Engine:	Kubota D722 20 hp/15 kW water cooled diesel engine with spark arrest
Pump:	Vane type, Jupop R260 363 CFM @ FREE AIR and 304 CFM @ 18 inch Hg
Max Inlet Vacuum:	28.5 inch Hg / 0.965 bar
Suction Head:	32 ft / 9.84 m
Frame:	Steel cage, shot blasted and epoxy painted, fork pockets
Lifting:	Central lift point fitted
Dimensions	70 x 41 x 70 inches / 178 x 104 x 178 cm
Features:	21 gallon / 79 L fuel tank, Clutch for disconnecting drive

Options:

Suction wand, Hose set includes 2 x Vacuum hoses each 3 inch x 15ft / 75mm x 4.6m plus 1 x suction hose 2 inch x 15ft / 50mm x 4.6m. 3x2" reducer, 100 gallon vacuum tank, vacuum hopper

Optional Accessories



110 gallon All Terrain Vacuum Tank



Removable chassis makes trailer transportation easy.



Vacuum Hopper