# ELASTEC MPATV

Multi-Purpose All Terrain Vehicle







**Base Vehicle Specification** 

Engine	3 cylinder diesel, 21.6 hp / 16 kW, 54.8 cu. in / 898 cc
Fuel Tank	7.4 gallon / 28 litre
Transmission	Variable hydro transmission
Max. Speed	25 mph / 40 kmh
Differential Lock	Foot operated
Gears	Hi-Med-Lo range
Brakes	Disc
Steering	Hydrostatic power
Suspension	Mac-Pherson Strut / DeDion axle
Towing Capacity	1,300 lb / 590 kg
Payload Capacity	1,576 lb / 715 kg
Weight	1,984 lb / 900 kg (without accessories / mods)
Cargo Bed	52 x 46 inch / 1.32 x 1.18 m, max load 1,102 lb / 500 kg
Sound Level	89 db(A) operator ear no load
Tires	25 x 10-12 HDWS 6 ply
Front Guard	Included
Body Color	Orange
Hydraulic Bed Tilt	Included

Elastec is the Worlds largest manufacturers of environmental response equipment. Recognizing that access to spill locations is often difficult and in remote areas, we have developed a range of customized response vehicles.

The Multi-Purpose All Terrain
Vehicle is a highly modified
Utility Vehicle that provides you
with the ultimate 4 wheel drive
utility vehicle capable of running
oil skimmers and submersible
pumps plus - lifting, towing and
transporting materials across
difficult off-road terrain such as
beaches, tundra and snow!

We have taken an industry standard platform and incorporated many features, you can add tracks and A-Frame with Winch, hydraulically driven accessories as an option.



## **Integrated Auxiliary Hydraulic System**



Stainless steel quick couplings (2 x pressure and common return line)

Hydraulic control block with filter, gauges and controls

12 gallon / 45.4 litre hydraulic tank with strainer, sight / temperature gauge

Optional hydraulic accessories; (submersible E150 pump, drum skimmer)



Tandem hydraulic pump providing flow of;

Circuit 1: 4.27 gpm / 16.2 lpm at 2,500 psi

Circuit 2: 5.40 gpm / 20.4 lpm at 2,500 psi

### **Towing**

The Multi-Purpose ATV has a towing capacity of 1300 lbs / 590 kg. Traction is greatly enhanced when tracks are fitted. We offer a variety of trailers and vacuum tank matched to this vehicle.

The optional four wheel drive track system creates a larger and more stable footprint. This makes the vehicle's mobility much more versatile than with conventional tires.

Note: track system model may vary.



# **Available Options**



### A-Frame Davit / Winch

Max Lifting Capacity	500 lb / 227 kg
Winch Data	3,000 lb / 1,360 kg
	rated line pull
	12V DC
	0.9 hp / 0.7 kw 3-Stage
	Planetary Geartrain
	136:1 Gear Ratio







**Pumps** 





1309 West Main St. Carmi, Illinois 62821, USA +1 (618) 382-2525 www.elastec.com elastec@elastec.com