

ELASTEC

PACS 286

Trailer Mounted Vacuum System



Oil Spill Equipment | Floating Barriers | Incinerators



Specification

Tank Capacity	800 gallons / 3,028 litres
Chassis	Trailer
Vacuum Tank Elevate	Included
Engine	24 hp / 18 kW Diesel
Vacuum Pump Type	Vane
Airflow (pulling vacuum)	150 cfm @ 27 Hg 254 cu.m/hr @ 900 mbar
Airflow (free air)	286 cfm 485 cu.m/hr
Vacuum Clutch	Yes
Pressurize Tank Facility	Yes
Rear Door	25 inch / 0.63 m
ShovelHead Skimmer	Optional
Empty Weight	4,960 lb / 2,250 kg
Gross Weight	12,000 lb / 5,443 kg
Dimensions (LxWxH)	207 x 80 x 99 inch 5.26 x 2.03 x 2.51 m

The PACS (Portable Air Conveyance System) is ideal for picking up non-hazardous liquids, solids, and sludge from land or water, it is suitable for use in remote areas and costs less than vacuum trucks.

Features

- Tandem axle trailer.
- Hydraulic hoist to raise tank for dumping contents.
- 2- Rear stabilizers.
- DOT approved safety chains and hooks.
- Trailer lights meet DOT standard lighting regulations and are sealed & weatherproofed in an enclosed central junction box.
- Storage box.
- Working lights.

Optional

- Suction Wand Assembly
- 2 inch x 20 ft Suction Hose



1309 West Main St.
 Carmi, Illinois 62821, USA
 +1 (618) 382-2525
www.elastec.com elastec@elastec.com