

ELASTEC PACS 424

Trailer Mounted Vacuum System



Oil Spill Equipment | Floating Barriers | Incinerators



Specification

| | |
|----------------------------|--|
| Tank Capacity | 1,000 gallons / 3,785 litres |
| Chassis | Trailer |
| Vacuum Tank Elevate | Included |
| Engine | 25 hp / 18 kW Diesel |
| Vacuum Pump Type | Water Cooled Vane |
| Airflow (pulling vacuum) | 324 cfm @ 18 Hg |
| Airflow (free air) | 424 cfm |
| Vacuum Clutch | Yes |
| Pressurize Tank Facility | Yes |
| Rear Door* | 36 inch / 0.91 m |
| High Pressure Water System | Optional |
| E150 Transfer Pump | Optional |
| Drum Skimmer | Optional |
| Dry Particulate Filter | N/A |
| ShovelHead Skimmer | Optional |
| Empty Weight | 5,930 lb / 2,689 kg |
| Gross Weight | 16,000 lb / 7,257 kg |
| Dimensions (LxWxH) | 219 x 86.5 x 99.5 inch 556 x 220 x 253 cm |

Equipped with a 25 hp / 18 kW diesel engine driving a Water Cooled Vacuum pump, capable of sustaining continuous levels of high vacuum without overheating. Free air 424 cfm / 324 under load, max vacuum 90% / 27 inch, max continuous vacuum 83% / 25 inch. Engine fitted with Spark Arrestor. Static grounding wire.

Standard Accessories

Three 15 ft / 4.5 m sections of vacuum hoses
Two 3 inch and one 2 inch
Suction wand and 3x6 inch camplock coupler

Optional

*Fully opening 60 inch / 1.5 m rear door
Spares kit, E150 Submersible Pump, hydraulically operated drum skimmer, high pressure water pump and tank



1309 West Main St.
Carmi, Illinois 62821, USA
+1 (618) 382-2525
www.elastec.com elastec@elastec.com