

ELASTEC
PACS 770

Trailer Mounted Vacuum System



Oil Spill Equipment | Floating Barriers | Incinerators



Specification

Tank Capacity	1,000 gallons / 3,785 litres
Chassis	Trailer
Vacuum Tank Elevate	Included
Engine	34 hp / 25 kW Diesel
Vacuum Pump Type	Air Cooled Blower
Airflow (pulling vacuum)	770 cfm @ 15 Hg
Airflow (free air)	920 cfm
Vacuum Clutch	Yes
Pressurize Tank Facility	No
Rear Door	36 inch / 0.91 m 60 inch / 1.5 m*
High Pressure Water System	Optional
E150 Transfer Pump	Optional
Drum Skimmer	Optional
Dry Particulate Filter	Standard
ShovelHead Skimmer	Optional
Empty Weight	5,780 lb / 2,622 kg
Gross Weight	16,000 lb / 7,257 kg
Dimensions (LxWxH)	219 x 86.5 x 99.5 inch 556 x 220 x 253 cm

Equipped with a 34 hp diesel engine, the vacuum blower delivers 770 CFM under load at 15 inch Hg vacuum / 920 CFM free air. Hydraulically lifted tank with 36 inch opening door for dumping sludges and solids. Heavy duty frame with wide flotation tires for off road use. With DOT approved lights and surge braking system for highway towing.

Optional

*Fully opening rear door, spares kit, E150 Submersible Pump, hydraulically operated drum skimmer, high pressure water pump and tank



1309 West Main St.
Carmi, Illinois 62821, USA
+1 (618) 382-2525
www.elastec.com elastec@elastec.com